Outstanding cooling performance even under extreme conditions










High Efficiency Tube

High Efficiency Tube

Increase the number of inner groove teeth from 45 to 54, which enlarges the heat transfer area and increases heat transfer efficiency up by 7.3%.





Turbo Mode

Turbo mode delivers cool and refreshing air with a single touch.



Remoter without ' Follow Me

Remoter with ' Follow Me

Follow Me, Sensitive Cooling for Your Surrounding

'Follow Me' keeps you comfortable by measuring the air temperature around you. Keep the remote close to you, and it will measure the surrounding temperature to deliver perfectly adjusted cooling.

Features -----

Diamond Cabine







Appearance _____



Ø

Prime Guard

Model	Indoor		MSAG-10CRN8	MSAG-13CRN8	MSAG-19CRN8	MSAG-25CRN8	
	Outdoor		MSAG-10CRN8	MSAG-13CRN8	MSAG-19CRN8	MSAG-25CRN8	
Cooling Capacity	Rated	Btu/h	9,700	12,300	18,500	24,200	
Power consumption	Rated	W	818	1,079	1,585	2,308	
Running current	Rated	A	3.56	4.69	6.89	10.03	
CSPF(Cooling seasonal performance factor) Wh/Wh		3.98	3.62	3.73	3.39		
Energy Efficiency Star F	Rating						
Power supply		V,Hz,Ph	220-240V~,50Hz,1Ph (power supply to indoor)				
Indoor unit	Indoor air flow (H)	m3/h(cfm)	580 (341)	600 (353)	820 (482)	933 (549)	
	Indoor Sound level (H/L)	dB(A)	41/30	41/30	43/33	46/41	
	Dimension(W*D*H)	mm	805x208x295	805x208x295	969x241x320	1083x244x336	
	Packing (W*D*H)	mm	875x375x285	875x375x285	1045x315x405	1155x415x315	
	Net/Gross weight	Kg	9.2/11.8	9.3/11.9	12.5/15.5	15/18.5	
Outdoor unit	Outdoor Sound level	dB(A)	51	52	56	58	
	Dimension(W*D*H)	mm	720x270x495	765x303x555	805x330x554	890x342x673	
	Packing (W*D*H)	mm	835x300x540	887x337x610	915x370x615	995x398x740	
	Net/Gross weight	Kg	25/26.8	27.3/29.7	38.9/41.5	49.1/52.4	
	Refrigerant Charge	g	R32/420g	R32/430g	R32/720g	R32/1200g	
	Design pressure	MPa	4.3/1.7	4.3/1.7	4.3/1.7	4.3/1.7	
Refrigerant piping	Liquid side/ Gas side	mm(inch)	Ø6.35/Ø9.52(1/4 [#] /3/8 [#])	Ø6.35/Ø9.52(1/4 [#] /3/8 [#])	Ø6.35/012.7(1/4º/1/2º)	06.35/012.7(1/4"/1/2")	
	Max. refrigerant pipe length	m	20	20	25	25	
	Max. difference in level	m	8	8	10	10	
Indoor-Outdoor connec	tion wiring (Not included)		3x1.5 mm ²	3x1.5 mm ²	3x2.5 mm ²	4x2.5 mm ²	
Power supply wiring(No	ot included wire)		3x1.5 mm ²	3x1.5 mm ²	3x2.5 mm ²	3x2.5 mm ²	

MSAG-10CRN8	MSAG-13CRN8	MSAG-19CRN8	MSAG-25CRN8	
MSAG-10CRN8	MSAG-13CRN8	MSAG-19CRN8	MSAG-25CRN8	
9,700	12,300	18,500	24,200	
818	1,079	1,585	2,308	
3.56	3.56 4.69		10.03	
3.98	3.62	3.73	3.39	
	220-240V~,50Hz,1Ph (power supply to indoor)		
580 (341)	600 (353)	820 (482)	933 (549)	
41/30	41/30	43/33	46/41	
805x208x295	805x208x295	969x241x320	1083x244x336	
875x375x285	875x375x285	1045x315x405	1155x415x315	
9.2/11.8	9.2/11.8 9.3/11.9		15/18.5	
51	52	56	58	
720x270x495	720x270x495 765x303x555		890x342x673	
835x300x540	887x337x610	915x370x615	995x398x740	
25/26.8	25/26.8 27.3/29.7		49.1/52.4	
R32/420g	R32/430g	R32/720g	R32/1200g	
4.3/1.7	4.3/1.7	4.3/1.7	4.3/1.7	
06.35/09.52(1/4"/3/8")	5.35/09.52(1/4 [*] /3/8 [*]) 06.35/09.52(1/4 [*] /3/8 [*])		Ø6.35/012.7(1/4 ["] /1/2"	
20	20 20		25	
8	8	10	10	
3x1.5 mm ²	3x1.5 mm ²	3x2.5 mm ²	4x2.5 mm ²	
3x1.5 mm ²	3x1.5 mm ²	3x2.5 mm ²	3x2.5 mm ²	

Model	Indoor		MSAG-10CRN8	MSAG-13CRN8	MSAG-19CRN8	MSAG-25CRN8	
	Outdoor		MSAG-10CRN8	MSAG-13CRN8	MSAG-19CRN8	MSAG-25CRN8	
Cooling Capacity	Rated	Btu/h	9,700	12,300	18,500	24,200	
Power consumption	Rated	W	818	1,079	1,585	2,308	
Running current	Rated	A	3.56	4.69	6.89	10.03	
CSPF(Cooling seasonal performance factor) Wh/Wh		3.98	3.62	3.73	3.39		
Energy Efficiency Star F	Rating						
Power supply		V,Hz,Ph	220-240V~,50Hz,1Ph (power supply to indoor)				
Indoor unit	Indoor air flow (H)	m3/h(cfm)	580 (341)	600 (353)	820 (482)	933 (549)	
	Indoor Sound level (H/L)	dB(A)	41/30	41/30	43/33	46/41	
	Dimension(W*D*H)	mm	805x208x295	805x208x295	969x241x320	1083x244x336	
	Packing (W*D*H)	mm	875x375x285	875x375x285	1045x315x405	1155x415x315	
	Net/Gross weight	Kg	9.2/11.8	9.3/11.9	12.5/15.5	15/18.5	
Outdoor unit	Outdoor Sound level	dB(A)	51	52	56	58	
	Dimension(W*D*H)	mm	720x270x495	765x303x555	805x330x554	890x342x673	
	Packing (W*D*H)	mm	835x300x540	887x337x610	915x370x615	995x398x740	
	Net/Gross weight	Kg	25/26.8	27.3/29.7	38.9/41.5	49.1/52.4	
	Refrigerant Charge	g	R32/420g	R32/430g	R32/720g	R32/1200g	
	Design pressure	MPa	4.3/1.7	4.3/1.7	4.3/1.7	4.3/1.7	
Refrigerant piping	Liquid side/ Gas side	mm(inch)	Ø6.35/Ø9.52(1/4º/3/8º)	Ø6.35/Ø9.52(1/4 [*] /3/8 [*])	Ø6.35/012.7(1/4 ["] /1/2")	Ø6.35/012.7(1/4 [#] /1/2 [#]	
	Max. refrigerant pipe length	m	20	20	25	25	
	Max. difference in level	m	8	8	10	10	
Indoor-Outdoor connection wiring (Not included)			3x1.5 mm ²	3x1.5 mm ²	3x2.5 mm ²	4x2.5 mm ²	
Power supply wiring(Not included wire)			3x1.5 mm ²	3x1.5 mm ²	3x2.5 mm ²	3x2.5 mm ²	
Thermostat type			Wireless Remote Control (Wifi control, Wire control optional)				

1. The above design and specifications are subject to change of product improvement without prior notice.

The noise level data reflects the level in anechoic chamber.
All units are being tested and comply to ISO 5151, ISO 16358-1.

Midea Scott & English Electronics Sdn Bhd (194517-X) No. 16, Jalan Chan Sow Lin, 55200 Kuala Lumpur Tel: 03-9221 1033 Fax: 03-9221 7204 / 03-9221 1434 / 03-9221 3509

• PENANG No. 35, Jalan Perniagaan Gemilang 1, Pusat Perniagaan Gemilang, 14000 Bukit Mertajam, Pulau Pinang. Tel: 04-548 3938 Fax: 04-548 9698

• JOHOR No. 25, Jalan Seri Impian 1, Taman Impian Emas, 81300 Skudai, Johor. Tel: 07-562 4898 Fax: 07-557 7898

• PERAK No. 38, Persiaran Perindustrian Pengkalan 10, Kawasan Perindustrian Pengkalan, 31500 Lahat, Perak. Tel: 05-323 2529 Fax: 05-323 2529

• PAHANG No. 258, Ground Floor, Jalan Air Putih, Taman Air Putih Mewah, 25350 Kuantan, Pahang Darul Makmur. Tel: 09-560 6668 Fax: 09-09-560 5050 • MALACCA No. 385-L, Taman Peringgit Jaya, 75400 Peringgit, Melaka. Tel: 06-292 1940 Fax: 06-286 7107

• KOTA BHARU PT 1436, Ground Floor, Taman Koperatif, Tanjung Chat, 15300 Kota Bharu, Kelantan. Tel/Fax: 09-743 1202

• SABAH Lot 3, Lorong Kompleks BSA, Kompleks BSA Kolombong, 88450 Kota Kinabalu, Sabah. Tel: 088-421 428 Fax: 088-431 427

SARAWAK 1st Floor, Lot 8517, Stutong Commercial Centre, Jalan Stutong, 93350 Kuching, Sarawak. Tel: 082-363 167 Fax: 082-366 167




Remote Control



Outdoor Unit

Dealer's Stamp:





Xtreme Cool R32 Non Inverter Wall Mounted Split





Healthy -----

Experience the air magic with Super Ionizer

Upon starting up, the air magic built-in device generates ions to remove airborne bacteria and dust. Making sure every breath take in clean, fresh and healthy air.

Cold Catalyst Filter Dual Filtration Technology

Cold Catalyst filtration system thoroughly eliminates harmful substances and decomposes a variety of harmful gases, providing clean and healthy air for you.

STEP 1: High Density Pre Filter

Density pre filter can effectively prevent large particles such as pet hair, dust and other airborne particles.





STEP 2: Micro Protection Filter

Cold catalyst filter can catalyze the reaction of various harmful gases, such as formaldehyde, ammonia, benzene, TVOC and hydrogen sulfide.

Pollen (Allergen), smoke, micro dust(under 0.3um)



C₆H₆



Flower pollen



Convenience

Louver Position Memory Function

When you start the unit, the angle of horizontal louver will automatically move to the same position as you set previously.

Smart -----

Control Your AC, Anytime and Anywhere WIFI Control (Optional)

Wherever you are, you can keep your home comfortable using the Smart MideaAIR App.

Start up your air conditioner on the way home to enjoy crisp, cool air the moment you walk in the door. The possibilities for comfort and convenience are endless.



Plug in Smart Kit into the air conditioner display board to enjoy the Smart Technology.



Smart WiFi CONTROL Wherever You Are

Simply download the MideaAIR app to contro your home's air conditioning at anytime and peace of mind. Help your kids or grandparents operate the air conditioning, even when you're



Run an automatic physical exam of your AC unit to detect any potential malfunctions, and guard against failures.

Xtream Cool.indd 4-6







2-Ways Piping Connection Both left and right sides of the indoor unit are possible for outstretch of connective piping and drainage hose.




Refrigerant Leakage Detection

The system will stop operation automatically to ensure safety once the refrigerant leakage is detected.

Golden Fin

The golden finned hydrophilic coil efficiently prevents bacteria from breeding and spreadig, creating a healthy and comfortable environment. It can also improve heating efficiency by accelerating defrosting. The unique anti-corrosive gold plating can withstand salty air, rain and other corrosive elements.



golden coating shows better performance in all working conditions than the prototype with blue coated foil.

Diamond-Cut Outdoor Unit

The air outlet in the shape of an 'Archimedes' screw and the bionic blower wheel work together to reduce the noise generated by the outdoor unit of the air conditioner. The T-shaped top cover ensures the stable operation of the internal parts and the durability of the power system.



PrimeGuard™

Midea's PrimeGuard[™] is more resistant in oxidation & corrosion than ordinary fins for condensers to furnish a steadier and long-lasting performance. It can also efficiently prevent bacteria from breeding and oil stain from adhering, and withstand weather elements to enhance durability.



T-shape Casing Diamond-edged and

from the unit, ensuring stable operation of the interior. outlet and T-Shaped top cover together keep rain or sand away The Diamond-edged Casing, Archimedes' screwshaped air







Smart Sleep Curve

Set the most appropriate emperature curve for you and efault modes for selection, or ou can customize your own one

